

PrimeTrex



Save Cash with PrimeTrex's Low Overall Cost!

- Savings benefits include reduced user training with intuitive ATM-style interface.
- Low overall cost of ownership due to reliability, ease of operation, and TechTrex's Remote Software Management. Fast and easy upgrades of existing applications.

Easy-to-use, & Compact.

- Programmable LCD softkeys and hotkeys provide one-touch access to functions.
- Integrated, High-speed, Thermal Printer with our Clam Shell design which allows paper rolls to be dropped in place without feeding through slots & rollers simply and easily.
- Economic, compact, and stylish design won't clutter valuable counter space.
- Comes standard with 2 separate hardware memory chips that's upgradeable to 3. **Multi Application capable.**



Integrated LED backlight.



Graphical LCD 128 x 64/res.



Full Graphic Thermal Printer, 22+ lines/sec.

PrimeTrex

Specifications

Processor	16-bit CISC processor
Memory	1MB
Real Time Clock (RTC)	RTC has power backup for data retention while the external power is turned off.
Magnetic Stripe Card Reader (MSR)	ISO MSR will read Tracks 1-2 with option of track 3. JIS MSR is bi-directional and it will read Track 1.
Display	Graphical LCD with resolution 128 x 64.
Keypad	Software programmable. Integrated LED backlight.
Speaker	Integrated Multi-tone Speaker.
Full Graphic Thermal Printer	<ul style="list-style-type: none">•Clam Shell design•Number of dots per line: 384 Dots•Printing width: 48 mm•Paper width: 58 mm•Paper diameter: 2 ¼ inch•Printing speed: 22+ lines per second
Communication Options	PrimeTrex supports multiple communication ports: <ul style="list-style-type: none">•1 RS232 ports•Wired dial up modem 14400bps – V.21, V.22, V.22bis, V23, V.32, V.32bis, Bell 103 and Bell 212.•Supports both Synchronous and Asynchronous.
Power	AC/DC power adapter, external, 100-240V
Environmental Specifications	<ul style="list-style-type: none">•Operating Temperature 0°C to 40°C•Operating Humidity 10% to 90% non-condensing
Hardware Warranty	1 year
Size (L x W x H)	244mm x 138mm x 82mm



PrimeTrex is a low cost desktop POS terminal with an integrated Printer. PrimeTrex is operated using an external power supply. Processing transactions through conventional dial-up via PSTN. PrimeTrex is capable of processing transaction through IP using ConverTrex, our protocol converter.